



RAISE THE BAR

STEP UP

While talent is one key to dominating the most extreme terrain, the 2022 range of KTM EXC models features a dynamic combination of race-bred ergonomics and technology as an added benefit.

Class-leading performance across the range, precise handling and impressive adjustability mean everyone is catered for, from weekend warriors to orange-blooded racers.



KTM EXC RANGE

RACE-INSPIRED UPGRADES

DEVELOPMENT PRECISION

Maintaining their championship-winning traits, the updated for 2022 KTM EXC models bring a series of refined suspension settings to the fray, along with an all-new factory-racing inspired look and MAXXIS MaxxEnduro fitted tires as standard.



TIRES

New for 2022, the KTM enduro range is fitted with racespecification MAXXIS MaxxEnduro rubber as standard. These tires have been developed to provide all-day riding comfort, but with unparalleled levels of extreme offroad performance and improved puncture-resistance.





SUSPENSION

WP XPLOR suspension once again sets the standard when it comes to taking on the most extreme terrain imaginable. With a focus to improve high-speed performance, both the front fork and PDS shock have undergone several simple, yet significant, updates for the KTM EXC 2022 line up. The overall result? A firmer, more consistent set of suspension giving riders the confidence to push the extremes even further.



OVERCOME ALL OBSTACLES

THE KING OF HARD ENDURO

The KTM 300 EXC TPI is under the spotlight within the updated KTM EXC 2-Stroke range. For true enduro specialists, it represents the ultimate extreme-enduro package right out of

the crate. This means it delivers everything you'd expect, from lightweight handling and to torque-filled power delivery all matched with top-end componentry.



EXTREME 2-STROKE ENGINEERING

A NEW MEANING TO ALL-TERRAIN

The 2022 KTM EXC range boasts a stable of three 2-Stroke models, all filled with pure READY TO RACE capability. From the lively KTM 150 EXC TPI to the lightweight marvel KTM 250 EXC TPI and the all-out KTM 300 EXC TPI, these extreme machines have borne the knowledge, insights, and progression conceived from years of top-level competition. KTM 150 EXC TPI



TPI TECHNOLOGY

Found across the KTM EXC 2-Stroke range, the Transfer Port Injection (TPI) system makes use of two fuel injectors which spray the optimal amount of fuel into the rear transfer ports. This downstream injection guarantees excellent atomization of the fuel with the upstreaming airflow, resulting in a highly efficient burn rate and significantly reduced losses from unburned fuel.

TORQUE-FILLED, **TRACTABLE PERFORMANCE**

GEARING

The 2022 KTM 250 EXC TPI benefits from revised final drive gearing from 13:50 to 13:52, resulting in a dramatically improved low-end grunt for more traction when accelerating out of corners. This also makes lifting the front end over obstacles as simple as popping the clutch and hanging on.







RACE-HONED REFINEMENT

THE BEST OF BOTH WORLDS

The 2022 KTM 350 EXC-F fills a unique gap in the enduro motorcycle portfolio, merging 250-like agility and 450-like power into a cohesive and versatile package. With no

compromise in overall performance, the KTM 350 EXC-F continues to be a wildcard in enduro competition the world over.

RAW, UNTOUCHABLE PERFORMANCE

4-STROKE DOMINATION

KTM is no newbie when it comes to engineering state of the art 4-stroke enduro weaponry. Built to provide usable power throughout the rev range, while maintaining high-levels of reliability and accessibility, the 2022 KTM EXC-F range is ready to take on any trail.




KTM 500 EXC-F



RACE-WINNING TORQUE & POWER

ENGINES

Compact, and churning out class-leading performance, KTM's fuel-injected 4-stroke engines are the most refined and powerful on the market. Making use of enduro-specific exhaust systems and intelligent electronic fuel-injection technology, the engines sit on the top step of the 4-Stroke powerplant podium.









INTERNATIONAL RACE ACCLAIM

KTM EXC SIX DAYS 2022

Enduro racing runs in the DNA of these special edition KTM EXC models. Boasting the very latest in innovation, the KTM EXC SIX DAYS models are the most dedicated, READY TO RACE enduro motorcycles available on the market today.









KTM POWERPARTS

ENHANCED INTENSITY

Using materials sourced from the world of top-level offroad racing, such as carbon fiber, titanium and high-strength anodization processes, each item in the KTM PowerParts list has been engineered for riding at the very edge.

01 FACTORY FRONT WHEEL 1,6×21"

Anodized D.I.D DirtStar rim, developed to produce the ideal compromise between rigidity and flexibility.

02 FACTORY TRIPLE CLAMP

Manufactured from the highest-grade aluminum and tuned to produce perfect steering stem stiffness and flexibility – adapted precisely to the WP fork.

03 FMF TITAN POWERCORE 2.1 SILENCER


Fully made of high-grade treated titanium which allows enriched sound and extremely low weight compared to the stock silencer.

04 WAVE BRAKE DISC

Floating system enable flawless brake control and minimal wear on brake pads.

05 AKRAPOVIČ "SLIP-ON LINE"

Akrapovič slip-on silencer offers more power and torque, uncompromising factory racing looks, and substantial weight savings.



> VISIT KTM.COM TO VIEW THE ENTIRE KTM POWERPARTS RANGE



KTM POWERWEAR

MADE FOR EXTREMES

KTM PowerWear has been designed to allow for the highest levels of performance while offering optimum protection for riders with all offroad riding or racing intentions.

A STRYCKER HELMET

Lightweight offroad helmet with elaborate ventilation system made exclusively for KTM.

B FURY GOGGLES

Advanced Enduro goggles with dedicated moisture management thanks to the three layer and fleece foam lining.

C RACETECH SHIRT

Robust quality and lightweight with breathable mesh panels for optimum ventilation, along with taped sleeve cuffs and elastic mesh collar.

D RACETECH GLOVES

Lightweight offroad gloves with touchscreen functionality and silicone print for better grip.

E RACETECH PANTS

Durable, lightweight offroad pants with heatproof and abrasion-resistant leather knee reinforcement and elasticized panels.

F TECH 7 EXC BOOTS

Made exclusively for enduro riding, with a non-slip two-component sole and a stainless steel heel and toe protection.

> VISIT KTM.COM TO VIEW THE ENTIRE KTM POWERWEAR RANGE



2-STROKE

4-STROKE

25











KTM 250 EXC TPI	KTM 300 EXC TPI

ENGINE (LIQUID COOLED)			
ENGINE TYPE	Single-cylinder, 2-stroke, Exhaust control	Single-cylinder, 2-stroke, Exhaust control	Single-cylinder, 2-stroke, Exhaust control
ENGINE MANAGEMENT	Continental TPI System	Continental TPI System	Continental TPI System
DISPLACEMENT	143.99 cc	249 cc	293.2 cc
BORE X STROKE	58 mm x 54.5 mm	66.4 mm x 72 mm	72 mm x 72 mm
COMPRESSION RATIO	-	-	-
STARTER/BATTERY	E-starter & kick-starter system/Lithium Ion 12V/2Ah	E-starter/Lithium Ion 12V/2Ah	E-starter/Lithium Ion 12V/2Ah
FUEL SYSTEM	Dellorto throttle body Ø 39 mm	Dellorto throttle body Ø 39 mm	Dellorto throttle body Ø 39 mm

TRANSMISSION

CLUTCH	Wet multi-disc DS clutch, Brembo hydraulics	Wet multi-disc DDS clutch, Brembo hydraulics	Wet multi-disc DDS clutch, Brembo hydraulics
LUBRICATION	Electronically regulated oil pump	Electronically regulated oil pump	Electronically regulated oil pump
GEARBOX	6 gears	6 gears	6 gears
GEAR RATIOS	12:33 15:31 17:28 19:26 21:25 20:20	14:32 16:26 20:25 22:23 25:22 26:20	14:32 16:26 20:25 22:23 25:22 26:20
PRIMARY RATIO/FINAL DRIVE	23:73/13:48 (13:50)	26:73/14:52 (13:52)	26:73/14:50 (13:50)
CHAIN	X-Ring 5/8 x 1/4"	X-Ring 5/8 x 1/4"	X-Ring 5/8 x 1/4"

CHASSIS & BRAKES

FRAME	Central double-cradle-type 25CrMo4	Central double-cradle-type 25CrMo4	Central double-cradle-type 25CrMo4	
SUBFRAME	Aluminum	Aluminum	Aluminum	
HANDLEBAR	NEKEN, Aluminum Ø 28/22 mm	NEKEN, Aluminum Ø 28/22 mm	NEKEN, Aluminum Ø 28/22 mm	
STEERING HEAD ANGLE	63.5°	63.5°	63.5°	
TRIPLE CLAMP OFSET	22 mm	22 mm	22 mm	
MUFFLER	Aluminum	Aluminum	Aluminum	
FRONT SUSPENSION	WP XPLOR USD fork, Ø 48 mm	WP XPLOR USD fork, Ø 48 mm	WP XPLOR USD fork, Ø 48 mm	
REAR SUSPENSION	WP XPLOR shock absorber with PDS	WP XPLOR shock absorber with PDS	WP XPLOR shock absorber with PDS	
SUSPENSION TRAVEL FRONT/REAR	300 mm/310 mm	300 mm/310 mm	300 mm/310 mm	
WHEELBASE	1,482 mm ± 10 mm	1,482 mm ± 10 mm	1,482 mm ± 10 mm	
RIMS FRONT/REAR	1.60 x 21"; 2.15 x 18" Giant	1.60 x 21"; 2.15 x 18" Giant	1.60 x 21"; 2.15 x 18" Giant	
TIRES FRONT/REAR	90/90-21"; 140/80-18"	90/90-21"; 140/80-18"	90/90-21"; 140/80-18"	
BRAKE FRONT/REAR	Disc brake Ø 260/220 mm	Disc brake Ø 260/220 mm	Disc brake Ø 260/220 mm	

DIMENSIONS & WEIGHT

SEAT HEIGHT/GROUND CLEARANCE	960 mm/370 mm	960 mm/370 mm	960 mm/370 mm
TANK CAPACITY	approx. 9 liters	approx. 9 liters	approx. 9 liters
DRY WEIGHT	approx. 96.8 kg	approx. 103.4 kg	approx. 103.4 kg









KTM	250	EXC-
-----	-----	------

KTM 350 EXC-F

KTM 450 EXC-F

KTM 500 EXC-F

Single-cylinder, 4-stroke, 4V/DOHC with finger followers	Single-cylinder, 4-stroke, 4V/DOHC with finger followers	Single-cylinder, 4-stroke, 4V/OHC with rocker arms	Single-cylinder, 4-stroke, 4V/OHC with rocker arms
Keihin EMS	Keihin EMS	Keihin EMS	Keihin EMS
249.91 cc	349.7 cc	449.9 cc	510.9 cc
78 mm x 52.3 mm	88 mm x 57.5 mm	95 mm x 63.4 mm	95 mm x 72 mm
13.8:1	13.5:1	12.75:1	12.75:1
E-starter/Lithium Ion 12V/2Ah	E-starter/Lithium Ion 12V/2Ah	E-starter/Lithium Ion 12V/2Ah	E-starter/Lithium Ion 12V/2Ah
Keihin throttle body Ø 42 mm	Keihin throttle body Ø 42 mm	Keihin throttle body Ø 42 mm	Keihin throttle body Ø 42 mm

| Wet multi-disc DDS clutch, Brembo hydraulics |
|--|--|--|--|
| Pressure lubrication with 2 oil pumps |
6 gears	6 gears	6 gears	6 gears
13:32 16:30 16:24 23:28 23:23 26:20	14:32 16:26 20:25 22:23 25:22 26:20	14:36 17:32 19:28 22:26 23:24 26:21	14:36 17:32 19:28 22:26 23:24 26:21
24:73/14:52 (13:52)	24:73/14:52 (13:52)	31:76/14:52 (13:52)	31:76/14:50 (13:50)
X-Ring 5/8 x 1/4"			


Central double-cradle-type 25CrMo4	Central double-cradle-type 25CrMo4	Central double-cradle-type 25CrMo4	Central double-cradle-type 25CrMo4
Aluminum	Aluminum	Aluminum	Aluminum
NEKEN, Aluminum Ø 28/22 mm			
63.5°	63.5°	63.5°	63.5°
22 mm	22 mm	22 mm	22 mm
Aluminum	Aluminum	Aluminum	Aluminum
WP XPLOR USD fork, Ø 48 mm			
WP XPLOR shock absorber with PDS			
300 mm/310 mm	300 mm/310 mm	300 mm/310 mm	300 mm/310 mm
1,482 mm ± 10 mm			
1.60 x 21"; 2.15 x 18" Giant			
90/90-21"; 140/80-18"	90/90-21"; 140/80-18"	90/90-21"; 140/80-18"	90/90-21"; 140/80-18"
Disc brake Ø 260/220 mm			

960 mm/355 mm	960 mm/355 mm	960 mm/355 mm	960 mm/355 mm
approx. 9 liters	approx. 9 liters	approx. 9.2 liters	approx. 9.2 liters
approx. 103 kg	approx. 103.8 kg	approx. 105.5 kg	approx. 105.6 kg

SIX DAYS EDITION AVAILABLE SIX DAYS EDITION AVAILABLE SIX DAYS EDITION AVAILABLE SIX DAYS EDITION AVAILABLE

SIX DAYS & ERZBERGRODEO EDITIONS AVAILABLE SIX DAYS EDITION AVAILABLE 24





YOUR ENDURO JOURNEY STARTS HERE

There has never been a better time to get onto a 2022 KTM EXC motorcycle. With a range of models to cater to every experience level, as well as proven pre and after-sales products, your journey to new extremes starts here.

Get all the information at KTM.COM



KTM FINANCE

Financing your ride couldn't possibly be any easier. With KTM's financial partner, finding yourself seated on the bike of your dreams is simpler than you could've ever imagined. Motorcycle specific, individually tailored financial solutions enable you to race off in no time. Contact your authorized KTM dealer for more information.

KTM Finance might not be available for all markets. Please ask your local authorized KTM dealer about the offers and conditions in your country.

KTM.COM





KTM SPORTMOTORCYCLE GMBH 5230 MATTIGHOFEN, AUSTRIA ©2021

LEGAL DISCLAIMER

Do not imitate! The riders illustrated are professional motorcycle riders. The photos were taken on closed racing circuits or closed roads. KTM wishes to make all motorcyclists aware that they need to wear the prescribed protective gear and always ride in a responsible manner in accordance with the relevant and applicable provisions of the road traffic regulations.

Only the homologated versions of the motorbikes promoted in this brochure are suitable for road use. The warnings and hazard notices in the owner's manual must be observed without fail when purchasing a motorcycle and using it for the first time (especially the prescribed speed limits). Some items in the KTM PowerParts product line are not approved for use on public roads in certain circumstances (varies from country). Please contact your KTM dealer for further information. The illustrated vehicles may vary in selected details from the production models and some illustrations feature optional equipment available at additional cost. All information concerning the scope of supply, appearance, services, dimensions and weights is non-binding and specified with the proviso that mistakes, printing, setting and typing errors may occur; such information is subject to change without notice. Please note that model specifications may vary from country to country.





